




- Liveview, Playback, Event
- Configuration



NUUO Crystal™ is the product that represents the next stage in VMS evolution. Rock solid, easily manageable, with powerful recording and viewing options available. Featuring revolutionary modular system structure that is made to handle middle to large project size, NUUO Crystal™ is the ideal choice for your enterprise. Featuring technology that focuses on delivering stable video recording performance, recording failover, and 3rd party integration choice, you will be impressed with the stability and flexible options with NUUO Crystal™.

Main Features

Server Highlight

- Linux based system
- Linux based intelligent video analysis
- Supports over 1200 camera models from more than 60 brands, and RTSP video stream ([Supported List](#))
- Records up to 64 megapixel cameras per Recording Server
- Supports throughput up to 250~550 Mbps (Depends on the quantity of Volume Group)
- Recording failover (available in Ultimate)
- Edge recording (available in Ultimate)
- Login Management Server via Active Directory user accounts (available in Ultimate)
- Metadata Server for 3rd Party Integration such as Point of Sale, Access Control, License Plate Recognition and Facial Recognition
- Diagnostic Service for retrieving important logs from both server and client for troubleshooting
- Web-based Hardware Health Check Tool for OS Storage Device and Hard Drive Disks
- Web-based Network Quality Evaluation Tool for checking the connection quality between server and cameras
- **Enterprise Management**
 - Built-in Management Server, Recording Server, Recording Failover Server and Metadata Server in one Crystal
 - Centralized I/O and event respond systems
 - Support NTP (Management Server can be a time server to make all system time consistent)
 - Volume group to distribute cameras to assigned volumes
 - Individual Retention Condition (IRC) per device
 - Video Device Utility: auto setup & bulk import
 - PTZ control priority
 - Powerful authorization for device permission and function privilege
 - System Navigator for connecting multiple management servers.
- **Stability**
 - Support RAID 0,1, 5, and 10
 - Support redundant power (CT-8000RP/ CT-8000EX-RP)
 - Support hardware watchdog and software watchdog
- **Open Platform**
 - ONVIF Profile compatible
 - Camera multiple stream support
 - Multiple codec support : H.265, H.264, MJPEG, MPEG4 and MxPEG
- **Value-added Benefits**
 - Stream up to 320ch live viewing connections per server to multiple clients simultaneously
 - Camera edge motion detection
 - Linux based video analytic

- Support continuous, scheduled, event based and I/O based recording
- Schedule-based and input-triggered boosting record
- Schedule-based user management
- Scheduled Backup video to FTP location
- Watermark for video verification
- Dual gigabit Ethernet ports





Client Highlight

- Cross platform for Windows, Mac and Linux (Linux System is binding with NuStation)
- All in one NuClient for remote configuring and viewing
- Unlimited channels of live view and playback
- Unlimited channels of NuMatrix Video Wall (available in Enterprise)
- System Navigator for centralized management for multi-sites and managing unlimited devices and events from multiple management servers on NuClient
- **Enterprise Management**
 - Centralized server upgrade for firmware and device pack
 - Bulk camera configuration
 - Centralized E-map
 - Centralized I/O Panel and Event Panel
 - Public and Private View/View profile for each user
 - View Tour to loop through selected Views
- **Open Platform**
 - Export video with 3rd party data overlay
 - Generic Fisheye Dewarp technology for all fisheye cameras
 - Panorama 360° PTZ - Immervision and fisheye camera
 - Support multiple stream profile
 - Auto-switch stream profile
- **Value-added Benefits**
 - Support mobile client for iPhone / iPad / Android
 - NUUO Image Fusion Technology - stitch up to 10 cameras together
 - Layout Wizard - customized layout for viewing
 - Instant Playback on live view, e-map and event list
 - Thumbnail in Playback Timeline
 - Twin Clients to support identical, full featured software client and web client
 - Support digital and optical PTZ
 - Support preset and patrol
 - Save video clips into AVI, ASF and MOV
 - Multi-Metadata source on video display

- Intelligent Search in playback
- Language switch capacity
- Hardware GPU Acceleration for


External Support

- External storage through DAS, iSCSI and NFS
 - * Support list http://www.nuuo.com/SupportCamera.php?node_id=12
- Support third party Point of Sale, Access Control, License Plate Recognition and Facial Recognition
- Support up to 256 NUUO I/O boxes per server (A08)
- Support APC Uninterrupted Power Supply (APC Smart-UPS 750 VA / APC Back-UPS 500 ES / APC Smart UPS 1500 / APC Smart UPS 3000)

Server						
Hardware Specifications						
Model	TR-0400CT	R1-0400CT	CT-8000R	CT-8000RP	CT-8000EX	CT-8000EX-RP
Product Image						
Type	Tower	Rackmount 1U	Rackmount 2U			
CPU	Intel Celeron J1900		Intel Core i5		Intel Core i7	
RAM	2G X 2 (Dual channel)		4G X 2 (Dual Channel)			
Number of Drives (hot swapping supported)	4 X SATA III		8 X SATA II			
Max Storage Per Drive**	10TB		10TB			
Max Internal Total Storage	40TB		80TB			
RAID Level	RAID 0, 1, 5, 10					
I/O Interface	2 X USB 2.0 (for mouse or UPS); 1 X USB 3.0; 1 X eSATA (for DAS) 1 X VGA; 1 X HDMI		2 X USB3.0; 2 X USB2.0 (for mouse or UPS); 1 X eSATA (for DAS); 1 X VGA			
LAN	2 x Gigabit Port, RJ45					
LAN Transmission Speed	10/100/1000 Mbps					
Voltage	100-240V					
Power Consumption	Full loading:50W Max: 250W	Full loading:50W Max: 250W	Full loading: 150W Max: 500W	Full loading: 160W Max: 500W	Full loading: 150W Max: 500W	Full loading: 160W Max: 500W
Device Dimension (H X W X D)	212 X 200 X 318 mm	45 X 447 X 429 mm	88 X 447 X 583 mm		88 X 447 X 583 mm	
Device Weight (Without Drive)	5.3 kg (11.7 lbs)	6.0 kg (13.2 lbs)	11.4 kg (25.1 lbs)	13.2 kg (29.1 lbs)	11.4 kg (25.1 lbs)	13.2 kg (29.1 lbs)

Temperature	Operating: 0°C-40°C		
Humidity	Operating: 5%-95%		
Certification	CE, FCC, CB, RoHS	CE, FCC, RoHS	
Software Specification			
Server Operating System	Linux		
License Type	Professional / Enterprise / Ultimate / Metadata channel licenses*		
Number of Cameras per Recording Server	64 CH		
Number of Stream Out per Recording Server	320 CH		
Number of Camera per NuClient	400 CH		
ONVIF Device Support	V		
Video Compression	H.265, H.264, MPEG4, MJPEG, MxPEG		
Multiple Stream Profile	V		
Recording Throughput	250 Mbps (MAX), 150 Mbps (OPTIMAL)	250 Mbps (1 Volume Group) 400 Mbps (2 Volume Groups) 550 Mbps (3 Volume Groups)	
3 rd Party Support	Point of Sale, Access Control, License Plate Recognition, Facial Recognition (Depends on plugin installed)		
Metadata Function	1. Live View and playback line by line with video 2. Metadata Search and Result Export 3. Multiple Metadata source on video		
Export	AVI, Original AVI, ASF, MOV		
Number of Live View Spot-out (Local display)	4CH per View, View tour to 64CH	16CH per View, View tour to 64CH	16CH per View, View tour to 64CH
Recording Type	Continuous record, trigger record by digital input, motion-triggered record, event-triggered record, boosting record, record by schedule, and manual trigger record on NuClient		
Event Pre-record and	V		

Post-Record					
Network Time Protocol (NTP)	V				
Joystick Support	V				
Supported IP Camera Brands	Supported Cameras				
	ACTi	ADEMCO	Alarm.com	American Dynamics	
	AMTK	Arecont	ATV	AXIS	
	Aver	BASLER	BOSCH	Brickcom	
	Bullwark	Canon	Centrix	CISCO	
	CNB	Dahua	D-Link	DlinkCN	
	DYNACOLOR	Eneo	Etrovision	Everfocus	
	FINE	Flir	Forenix	GE	
	GNS	Grundig	Guardeon	HIKVISION	
	Honeywell	IP power	Innotech	Jetstor	
	JVC	LevelOne	LG	MegaIP	
	Messo	MOBOTIX	MIWURMET	Netgear	
	Onvif	Panasonic	Pelco	RIVA	
	QVS	Samsung	SANTEC	Secubest	
	Shany	Sony	Sunell	TRENDnet	
	TRUEN	UDP	Vision Hi-Tech	Vista	
	VIVOTEK	WatchNET	Wavekrom	Zavio	
	3S vision				
	Supported Languages	Czech, Chinese(Simplified), Chinese(Traditional), English, Finnish, French, Germany, Italian, Japanese, Korean, Polish, Portuguese (Brazil), Russian, Spanish, Swedish, Thai, Turkish			
	* NUUO Crystal™ Ultimate, Enterprise, and Professional licenses are not compatible with each other. Only 1 type of license may be installed onto a single management server.				
** Refer NUUO web site for hard drive compatibility list (http://www.nuuo.com/SupportCamera.php?node_id=12)					

Client	
Open Platform System Minimum Requirement	
CPU	Intel Core 2 Duo, 2.6GHz
Display Card	NVIDIA or ATI with 1GB memory (OpenGL 2.0 and later)
OS Supported	Microsoft Windows
	Mac OS X
OS Supported	Windows XP (32-bit)
	Windows 7 (32/64-bit)
OS Supported	Windows 8.1 (32/64-bit)
	Windows 10 (64-bit)
RAM	2GB
LAN Transmission Speed	10/100/1000 Mbps (RJ45)
User Interface	<ul style="list-style-type: none"> ■ Application <ul style="list-style-type: none"> • NuClient • NuMatrix (Available with Enterprise/ Ultimate License) ■ Web browser <ul style="list-style-type: none"> • Internet Explorer 8, 9, 10, 11 (Web Client) • Firefox 23 to 42 (Windows version) • Google Chrome (Windows version) ■ iViewer for NUUO iPhone, iPad, and Android mobile
Notice	It is suggested to execute the remote client system on the 64-bit OS and 4G (2GB X 2) RAM for better performance.
Platform Binding Thin Client Solution	
Model	NU-16FHD
Product Image	
OS	Ubuntu
Embedded Application	NuClient
Flash Memory	eMMC 32GB
RAM	2X2GB
LAN Transmission Speed	10/100/1000 Mbps (RJ45)
I/O Interface	2 x HDMI; 4 x USB 3.0; 1 x SD Card Slot; 1 x headphone-out and mic in;
Power	AC 100~240V 12-19V DC-in 65W
Operational Temperature	System 0~45°C; Board 0~60°C
Operational Humidity	0%-90% (Non-condensing)
Dimensions (H X W X D)	27 x 140.8 x 107.5 mm
Device Weight	560g

Accessory	VESA mount		
Feature Highlight	Supports hardware decode 1080p 30FPS @16CH in H.264		
Notice	<div><div></div>The OS version shall not be upgraded or downgraded to any other version at will.<div></div>Unable to do hardware decode when doing “Motion Search” and “Export Video.”<div></div>Supports to export to .MOV as only format and unable to export H.265 Codec streaming.<div></div>Supports Live Viewing and Playback only for IVS.</div>		
License Level Specification			
Feature	Ultimate	Enterprise	Professional
Edge Recording	V		
LDAP/ MSAD	V		
Recording Failover	V		
Video Wall	V	V	
System Navigator	V	V	V
Diagnostic Service	V	V	V
NUUO Fisheye Dewarp	V	V	V
Central Management	V	V	V
Individual Retention Condition	V	V	V
Boosting Record	V	V	V
Multi-stream Setting	V	V	V
SDK Support	V	V	V
3 rd Party Support (Point of Sales / Access control / License Plate Recognition/ Facial Recognition)	V	V	V

Technical Details

• **System, Setting, Management and Integration**

- **Centralized Management:** Unlimited cameras, access control, POS and I/O devices for centrally configuring, user authority management, integrated video and 3rd party monitoring, system status overview, event handling, and cluster recording failover management.
- **System Navigator:** Use one NuClient to login multiple management servers. Watch videos from different recording servers under different management servers. Configuration on different management servers can also be accomplished.
- **Linux Based:** Stable, reliable and virus free.
- **Camera Integration:** Open platform support multiple camera brands, models and RTSP stream, UPnP search and ONVIF ProfileS. Centrally configure camera parameters including video format, resolution, frame rate, and lens setting.
- **Multiple and High Channel Streaming:** Stream up to 256 connections per server to multiple clients simultaneously for live view. Support multiple stream profile from cameras, displaying lower bit rate but still record with good quality.
- **All Services in One NUUO Crystal™:** Built in Management Server, Recording Server, Recording Failover Server, and Metadata Server in one NUUO Crystal™. Enable necessary services to meet different system scope and demand.
- **Authorization Management:** Manage function privilege, device access permission and priority with unlimited roles, users and user groups.
 - LDAP/ MSAD accounts login support
 - Customized login period by users
 - Privilege by function
 - Access permission by device
 - PTZ control priority
 - Priority for Video Wall control
- **Recording Failover Server Group (available in Ultimate):** Flexible N+M server cluster structure to maximize system reliability, uptime, and efficiency.
- **Linux Intelligent Video Analytic (optional license):** support 4 different license type: presence, counting, surveillance and advanced.
 - Counting
 - Tamper
 - Camera calibration
 - Object classification
 - Camera shake elimination
 - Presence(tripwire)
 - Enter and Exit
 - Appear and disappear
 - Dwell
 - Tailgating
 - Stop

- Direction
- Abandoned/Removed object

- **Third Party Integration:** Integrate third party data and video on unified management platform. The plugin structure allows user extend the system by plugin installing.
- **Schedule-Based Architecture:** Unified Schedule Profile for event, user's login duration, recording schedule, recording parameter and 3rd party streaming for complicate environment and requirement.
- **Multiple Video Codec Support:** NUUO Crystal™ supports H.265, H.264, MJPEG, MPEG4 and MxPEG for best quality and storage usage.
- **Video Device Utility:** Utility offers camera auto setup function and bulk import camera list.
- **Event/ Action Management:** Centrally manages events from system, cameras, 3rd party metadata devices, and I/O devices with instant alert responses. Event and boost record reduce storage usage but ensure important period recording.
 - **Event**
 - System event
 - Server disconnect
 - Fail to write to drive
 - Volume operation error
 - Volume Group no functional volume
 - Recording Module error
 - Power Failed (Redundant power)
 - Auto Backup Failed
 - No available Failover Server for disconnected Recording Server (available in Ultimate)
 - Camera event
 - Camera Motion Detection
 - Connection lost
 - No enough space for retention days
 - IVS event
 - Counting event
 - Presence
 - Enter/Exit
 - Appear/disappear
 - Dwell
 - Tailgating
 - Stop
 - Direction
 - Abandoned/Removed object
 - Tamper
 - Digital input event
 - Input signal on
 - 3rd party metadata event
 - Transaction Start
 - Transaction Stop
 - Up to 10 user-definable events
 - **Action**
 - Auto Video Popup to NuClient and NuMatrix when event happens
 - Video edge display on client
 - NuClient play alert sound
 - Send E-mail
 - Camera go to preset point

- Trigger Digital Output

- **Centralized System Status Overview:** Real-time monitoring the status of all servers, cameras, IO devices, and metadata channels.
- **Automatic NUUO Crystal™ Search:** Automatically search for all NUUO Crystal™ in the network.
- **Automatic Camera Model Detection:** Automatically search for IP cameras in the network (camera should support UPnP protocol) or manually insert it. Auto detection help users to find the brand and model of the camera after specifying its IP address.
- **Dual Gigabit Ethernet Ports:** NUUO Crystal™ is equipped with 2x gigabit ports. User can separate the recording stream from viewing stream to ensure the cleanest recording pipeline.
- **I/O Event Control:** With the integration of camera I/O and NUUO I/O Box, system can start recording or trigger instant alert when input triggered, or trigger output as an event happened.
- **License Management:** Extendable license activation for up to 64CH per Recording Server, and unlimited channel per system. Supports online/ offline activation and transfer. It is scalable to upgrade system from Enterprise to Ultimate by simply activate upgrade license.
- **NTP Date/ Time Synchronization:** The system can interface to Internet Time Server (NTP server) for time and date synchronization at each location. Management Server can play the role as NTP server on LAN environment.
- **Watchdog:** Support software watchdog and hardware watchdog to system stability.
- **Diagnostic Service:** A simple tool to retrieving important logs both from servers and clients for troubleshooting.

• Recording, Recycle and Storage:

- **High Recording Throughput (250Mbps for Single Volume):** Process large amount of data throughput boost Crystal's recording performance to 250 Mbps for single volume, about 64CH 5-Megapixel cameras (H.264, 15 fps, moderate traffic). Volume group mechanism can further increase the throughput.
- **Volume Group:** Volume Group mechanism distributes camera throughput loading to multiple volume groups so that further enlarges recording throughput. It can also maximize recording spec or have different levels of data protection

*Throughput testing result:

- Total 250 Mbps for 1 Volume Group per CT-8000/CT-8000R
- Total 400 Mbps for 2 Volume Group per CT-8000/CT-8000R
- Total 550 Mbps for 3 Volume Group per CT-8000/CT-8000R

- **Individual Recycle Condition (IRC) Per Device:** NUUO Crystal™ supports individual recycle condition (IRC) for each video or metadata device. Videos within specified retention time periods will be protected from recycling deletion. Videos outside the retention time periods will be automatically deleted. When system reaches storage capacity limit, even video data within IRC retention periods will still be deleted to free up additional storage space for Recording. Users will be notified when this occurs.
- **RAID:** Support RAID 0, 1, 5 and 10 for maximum capacity or data protection at the HDD level.
- **Multiple Recording Modes:** NUUO Crystal™ supports multiple event-based and schedule-based recording modes. It also supports pre-event and post-event record to make sure seamless protection.

*Supported recording mode:

- Continuous record
- Digital-Input-triggered record
- Motion-triggered record
- Event-triggered record
- Boosting record
- Record by schedule
- Manually triggering record on NuClient
- Edge Recording

■ **External Storage:** Support SAN (iSCSI), NFS and DAS (eSATA).

■ **Edge Motion:** Support camera edge motion detection, reduce server loading and ensure stability. With event-action management and recording mode in NUUO Crystal™, user can monitor system easily.

■ **Audio:** Support camera audio and audio recording.

■ **Watermark:** Protect original recording from alternation with our watermark verification tool.

• Remote Operation:

■ **Unified NuClient:** Simply login Management Server on NuClient to configure, live view or query video from all servers on the system. Support identical, full featured software client application and web client by browser.

■ **Cross Platform:** NuClient and Video Wall support both Windows and Mac OS. The web client support both IE browser and Windows Firefox.

■ **Video Wall (NuMatrix):** Support unlimited number of Video Walls and video displays, with up to 100CH display per monitor. Easily drag and drop view and cameras to Video Wall (available in Enterprise).

■ **Unlimited Channels monitoring:** The system support unlimited client connection and unlimited live viewing/playback display. It manages up to 400 channels live view and 100 channels playback simultaneously per view.

■ **NUUO Image Fusion Technology:** Manipulating camera views by changing its viewing angle and image size, making viewing easier in both live view and playback. Moreover, users can stitch multiple cameras together to form a unified single view.

■ **Layout Wizard:** Intuitive layout customization to meet needs for panorama cameras and camera corridor mode.

■ **Centralized I/O Management:** Manage all I/O devices on one I/O panel. Control I/O for event detection, instant action and digital output.

■ **Centralized Event Management:** View and search all event on one event panel. Video will pop up by double clicking the event.

■ **View Management:** Including View group, View tour, device group and Matrix profile, NUUO Crystal™ supports public view for all users and private view for each user. It also supports View Tour to loop through different selected Views.

■ **PTZ Control:**

- Support physical Pan/Tilt/Zoom, camera preset point and Patrol
- PTZ/Preset/Patrol control privilege and priority by device
- Support digital PTZ. Easily monitor one camera on multiple grid with different zone to enlarge the usability of megapixel cameras
- Event trigger camera goes to specific preset point
- NUUO Dewarp 2.0-- Generic fisheye dewarp for all fisheye camera integrated
- Support Immervision and fisheye cameras

■ **Instant Playback:** User can view instantly play the last few minutes of video via double click event, E-Map notification, or video tool bar. The intuitive GUI enable users easily export instant playback video or sync to

Playback.

- **Multi-View:** NUUO Crystal™ can duplicate the same live view video onto multiple channels and digitally zoom in to see the details of different spots on cloned channels without losing the original live view video.
- **NUUO Dewarp 3.0 Module**
 - Generic dewarp technology to process all types of fisheye-warp video.
 - Manual calibration for precise dewarp video
 - Client display supports 4 modes: Original mode, PTZ mode, Quad mode and Perimeter mode.
 - GPU acceleration to increase dewarp performance
 - Camera pre-calibration for dewarp accuracy
- **Joystick:** Utilize joystick and keyboard to control cameras physical PTZ and software enabled digital PTZ function.
- **Snapshot:** Easily take snapshot in BMP/JPEG during live viewing or playback. User can also take snapshot for whole View.
- **Centralized E-Map:** Tree structured E-Map with unlimited map layers. Supports intuitive GUI indicators of cameras, I/O devices, POS, Access Control and all server locations to have real-time system monitor. Supports notification on indicator when event happened, double click popup live video and instant playback, drag and drop cameras from map into live view, and one click exam device property.
- **Auto-switch Stream Profile:** Automatically switch stream profile base on the grid layout to fulfill both need of best quality of viewing and the loading of client computer.

• Playback, Search, Export and Secure Data

- **Intuitive Interface:** Browse video with GUI timeline and intuitive interface of playback, reverse playback, skip forward/backward, speed up/down, and play by speed shuttle.
- **Intelligent Search:** Intuitive post-event motion search for suspicious areas on video and post-event 3rd party data keyword search then query related camera recording. The system can also search events and double clicking query associated recording to quickly figure out flagged events.
- **Thumbnail:** Support thumbnail in playback timeline for easier evidence finding.
- **Event Search/Filter:** Support events filter function to enhance the speed of event search.
- **Evidence Export:** Export video or third party device data in AVI Snapshot and print video image in BMP/ JPEG with password and watermark.
- **Backup:** Support automatically backup videos to FTP and manually backup video from any recording servers.
- **Post-Recording Processing:** Support Intelligent search, Image fusion, digital PTZ, and Panorama 360° PTZ.

• External Device

- **Remote I/O Modules:** Analog devices that are connected to NUUO I/O Modules are converted to Ethernet through a media converter which enables NUUO Crystal™ to starting recording when inputs are triggered, or trigger outputs when an event occurred.
- **Redundant Power Supply:** CT-8000RP supports internal redundant power supplies. This ensures seamless operation even when the primary power supply has failed. Failed power supplies can be replaced while system is still operating.
- **APC UPS:** NUUO Crystal™ support external UPS (Uninterrupted Power Supply) power supplies which provide clean uninterruptable power.